

1001 G Street, N.W.
Suite 500 West
Washington, D.C. 20001
tel. 202.434.4100
fax 202.434.4646

RECEIVED
OPPT CBIC

2014 DEC 30 PM 3: 36

December 30, 2014

Writer's Direct Access
David G. Sarvadi
(202) 434-4164
sarvadi@khlaw.com

Via Hand Delivery

TSCA Confidential Business Information
Center (7407M)
Courier Deliveries:
1201 Constitution Avenue, NW
WJC East; Room 6428
Washington, DC 20004-3302

CBIC Control Number
363196

Re: Submission of Information Concerning Allegations of Environmental Contamination

Dear TSCA Section 8(e) Coordinator:

On behalf of Saint-Gobain Performance Plastics Corporation (SGPP), we are submitting this notice to provide information to the U.S. Environmental Protection Agency (EPA) concerning data regarding the presence of perfluorooctanoic acid (PFOA) that was detected in recent tests of the public drinking water supplies of the Village of Hoosick Falls, New York (the Village). SGPP processes fluoropolymers at a facility within the Village that were made with PFOA, but it is not and never has been a manufacturer, processor, distributor or user of PFOA *per se* anywhere in the United States. Since 2003 SGPP has participated in industry's voluntary PFOA phase-out effort by purchasing raw materials with decreasing levels of PFOA as an ingredient.

On December 12, 2014, SGPP became aware of PFOA measurements conducted by the Village in three wells used to supply drinking water to the community. The wells are located near one of our facilities in the Village. On December 15, 2014, SGPP learned of the results of the tests, and obtained a copy of the report. A copy is attached.

EPA has established a provisional health advisory (PHA) level for PFOA of 0.4 micrograms per Liter in drinking water. Even though health advisories serve as guidance only and are not enforceable, SGPP is reporting this information because the measurement from one of the wells exceeds this PHA. SGPP has been told that this one well has been removed from service, but SGPP has no further information at this time about the report, the apparent presence of PFOA in the wells, or about the laboratory that performed the tests.

SGPP has no information as to whether a significant risk of injury to human health or the environment is actually presented by the findings. Nonetheless, out of an abundance of caution

KELLER AND HECKMAN LLP

TSCA Confidential Business Information Center (7407M)

December 30, 2014

Page 2

and as a matter of good product stewardship we think it prudent to submit this information to EPA under section 8(e) of the Toxic Substances Control Act (15 U.S.C. § 2601 *et seq.*).

We trust that the Agency finds this information useful. If you have any questions, please contact Lauren Alterman, Vice President – Health, Safety & Environment of Saint-Gobain Corporation (parent of Saint-Gobain Performance Plastics Corporation), at (610) 341-7838.

Respectfully submitted,

A handwritten signature in black ink, appearing to read "David G. Sarvadi". The signature is written in a cursive style with a prominent flourish at the end.

David G. Sarvadi
Counsel to Saint-Gobain

Enclosure

cc: Ms. Lauren Alterman, Saint-Gobain

12/1/14

Lab Analysis Results

EPA range is measured in micrograms per liter.
Lab analysis was measured in nanograms per liter.

micrograms per liter = ppb (parts per **billion**)
nanograms per liter = ppt (parts per **trillion**)

The EPA benchmark range converted from micrograms per liter to nanograms per liter=
0.2 - 0.4 micrograms per liter = 200 - 400 nanograms per liter.

Results from the samples to date:

Sample 1 Pre-treated:	Well 3	Well 6	Well 7
	230	280	540

Sample 2 Pre-treated:	170	280	450
-----------------------	-----	-----	-----

Sample 1 Treated = 440

Sample 2 Treated = TBD

As a result of Sample 1, well 3 replaced well 7 as the prime water supply.

110 South Hill Street
 South Bend, IN 46617
 Tel: (574) 233-4777
 Fax: (574) 233-8207
 1 800 332 4345

Laboratory Report

Client: Village of Hoosick Falls
 Attn: Jim Hurlburt
 240 Main Street
 Hoosick Falls, NY 12090

Report: 326785
 Priority: Standard Written
 Status: Final
 PWS ID: Not Supplied
 Lab ELAP #: 11398

Copies to: None

Sample Information					
EEA ID #	Client ID	Method	Collected Date / Time	Collected By:	Received Date / Time
3116530	Well #3	537	10/02/14 08:35	Client	10/03/14 10:45
3116531	Well #6	537	10/02/14 08:52	Client	10/03/14 10:45
3116532	Well #7	537	10/02/14 08:25	Client	10/03/14 10:45

Report Summary

Detailed quantitative results are presented on the following pages. The results presented relate only to the samples provided for analysis.

We appreciate the opportunity to provide you with this analysis. If you have any questions concerning this report, please do not hesitate to call Nathan Trowbridge at (574) 233-4777.

Note: This report may not be reproduced, except in full, without written approval from EEA.

Digitally signed by Nathan Trowbridge
 Date: 2014.10.16 11:37:33 -04'00'

Authorized Signature

Title

Date

Client Name: Village of Hoosick Falls

Report #: 326785

Sampling Point: Well #3

PWS ID: Not Supplied

EEA Methods

Analyte ID #	Analyte	Method	Reg Limit	Result	Unit	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537	90	< 90	ng/L	10/08/14 07:40	10/09/14 09:02	3116530
375-85-9	Perfluoroheptanoic acid (PFHpA)	537	10	< 10	ng/L	10/08/14 07:40	10/09/14 09:02	3116530
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537	30	< 30	ng/L	10/08/14 07:40	10/09/14 09:02	3116530
375-95-1	Perfluorononanoic acid (PFNA)	537	20	< 20	ng/L	10/08/14 07:40	10/09/14 09:02	3116530
1763-23-1	Perfluorooctane sulfonate (PFOS)	537	40	< 40	ng/L	10/08/14 07:40	10/09/14 09:02	3116530
335-67-1	Perfluorooctanoic acid (PFOA)	537	20	230	ng/L	10/08/14 07:40	10/09/14 09:02	3116530

Sampling Point: Well #6

PWS ID: Not Supplied

EEA Methods

Analyte ID #	Analyte	Method	MRL†	Result	Unit	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537	90	< 90	ng/L	10/08/14 07:40	10/09/14 09:33	3116531
375-85-9	Perfluoroheptanoic acid (PFHpA)	537	10	< 10	ng/L	10/08/14 07:40	10/09/14 09:33	3116531
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537	30	< 30	ng/L	10/08/14 07:40	10/09/14 09:33	3116531
375-95-1	Perfluorononanoic acid (PFNA)	537	20	< 20	ng/L	10/08/14 07:40	10/09/14 09:33	3116531
1763-23-1	Perfluorooctane sulfonate (PFOS)	537	40	< 40	ng/L	10/08/14 07:40	10/09/14 09:33	3116531
335-67-1	Perfluorooctanoic acid (PFOA)	537	20	280	ng/L	10/08/14 07:40	10/09/14 09:33	3116531

Sampling Point: Well #7

PWS ID: Not Supplied

EEA Methods

Analyte ID #	Analyte	Method	Reg Limit	Result	Unit	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537	90	< 90	ng/L	10/08/14 07:40	10/09/14 10:04	3116532
375-85-9	Perfluoroheptanoic acid (PFHpA)	537	10	10	ng/L	10/08/14 07:40	10/09/14 10:04	3116532
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537	30	< 30	ng/L	10/08/14 07:40	10/09/14 10:04	3116532
375-95-1	Perfluorononanoic acid (PFNA)	537	20	< 20	ng/L	10/08/14 07:40	10/09/14 10:04	3116532
1763-23-1	Perfluorooctane sulfonate (PFOS)	537	40	< 40	ng/L	10/08/14 07:40	10/09/14 10:04	3116532
335-67-1	Perfluorooctanoic acid (PFOA)	537	20	540	ng/L	10/08/14 07:40	10/09/14 13:41	3116532

† EEA has demonstrated it can achieve these report limits in reagent water, but can not document them in all sample matrices,

Reg Limit Type: MCL SMCL AL
 Symbol:

Lab Definitions

~~Continuing Calibration Check Standard (CCC) / Continuing Calibration Verification (CCV) / Initial Calibration Verification Standard (ICV) / Initial Performance Check (IPC) - is a standard containing one or more of the target analytes that is prepared from the same standards used to calibrate the instrument. This standard is used to verify the calibration curve at the beginning of each analytical sequence, and may also be analyzed throughout and at the end of the sequence. The concentration of continuing standards may be varied, when prescribed by the reference method, so that the range of the calibration curve is verified on a regular basis.~~

Internal Standards (IS) - are pure compounds with properties similar to the analytes of interest, which are added to field samples or extracts, calibration standards, and quality control standards at a known concentration. They are used to measure the relative responses of the analytes of interest and surrogates in the sample, calibration standard or quality control standard.

Laboratory Duplicate (LD) - is a field sample aliquot taken from the same sample container in the laboratory and analyzed separately using identical procedures. Analysis of laboratory duplicates provides a measure of the precision of the laboratory procedures.

Laboratory Fortified Blank (LFB) / Laboratory Control Sample (LCS) - is an aliquot of reagent water to which known concentrations of the analytes of interest are added. The LFB is analyzed exactly the same as the field samples. LFBs are used to determine whether the method is in control.

~~Laboratory Method Blank (LMB) / Laboratory Reagent Blank (LRB) - is a sample of reagent water included in the sample batch analyzed in the same way as the associated field samples. The LMB is used to determine if method analytes or other background contamination have been introduced during the preparation or analytical procedure. The LMB is analyzed exactly the same as the field samples.~~

~~Laboratory Trip Blank (LTB) / Field Reagent Blank (FRB) - is a sample of laboratory reagent water placed in a sample container in the laboratory and treated as a field sample, including storage, preservation, and all analytical procedures. The FRB/LTB container follows the collection bottles to and from the collection site, but the FRB/LTB is not opened at any time during the trip. The FRB/LTB is primarily a travel blank used to verify that the samples were not contaminated during shipment.~~

~~Matrix Spike Duplicate Sample (MSD) / Laboratory Fortified Sample Matrix Duplicate (LFSMD) - is a sample aliquot taken from the same field sample source as the Matrix Spike Sample to which known quantities of the analytes of interest are added in the laboratory. The MSD is analyzed exactly the same as the field samples. Analysis of the MSD provides a measure of the precision of the laboratory procedures in a specific matrix.~~

~~Matrix Spike Sample (MS) / Laboratory Fortified Sample Matrix (LFSM) - is a sample aliquot taken from field sample source to which known quantities of the analytes of interest are added in the laboratory. The MS is analyzed exactly the same as the field samples. The purpose is to demonstrate recovery of the analytes from a sample matrix to determine if the specific matrix contributes bias to the analytical results.~~

~~Quality Control Standard (QCS) / Second Source Calibration Verification (SSCV) - is a solution containing known concentrations of the analytes of interest prepared from a source different from the source of the calibration standards. The solution is obtained from a second manufacturer or lot if the lot can be demonstrated by the manufacturer as prepared independently from other lots. The QCS sample is analyzed using the same procedures as field samples. The QCS is used as a check on the calibration standards used in the method on a routine basis.~~

~~Reporting Limit Check (RLC) / Initial Calibration Check Standard (ICCS) - is a procedural standard that is analyzed each day to evaluate instrument performance at or below the minimum reporting limit (MRL).~~

~~Surrogate Standard (SS) / Surrogate Analyte (SUR) - is a pure compound with properties similar to the analytes of interest, which is highly unlikely to be found in any field sample, that is added to the field samples, calibration standards, blanks and quality control standards before sample preparation. The SS is used to evaluate the efficiency of the sample preparation process.~~



110 South Hill Street
 South Bend, IN 46617
 Tel: (574) 233-4777
 Fax: (574) 233-8207
 1 800 332 4345

Laboratory Report

Client: Village of Hoosick Falls
 Attn: Jim Hurlburt
 240 Main Street
 Hoosick Falls, NY 12090

Report: 328480
 Priority: Standard Written
 Status: Final
 PWS ID: Not Supplied
 Lab ELAP #: 11398

Copies to: None

Sample Information

EEA ID #	Client ID	Method	Collected Date / Time	Collected By:	Received Date / Time
3133280	Water Plant Finished Water	537	11/04/14 08:45	Client	11/05/14 09:45
3133281	Well #7 Raw Water	537	11/04/14 09:05	Client	11/05/14 09:45
3133282	Well #3 Raw Water	537	11/04/14 09:40	Client	11/05/14 09:45
3133283	Well #6 Raw Water	537	11/04/14 10:10	Client	11/05/14 09:45

Report Summary

Detailed quantitative results are presented on the following pages. The results presented relate only to the samples provided for analysis.

We appreciate the opportunity to provide you with this analysis. If you have any questions concerning this report, please do not hesitate to call Nathan Trowbridge at (574) 233-4777.

Note: This report may not be reproduced, except in full, without written approval from EEA.

Digitally signed by Nathan Trowbridge
 Date: 2014.11.21 10:01:35 -05'00'

Authorized Signature

Title

Date

Client Name: Village of Hoosick Falls
 Report #: 328480

Client Name: Village of Hoosick Falls

Report #: 328480

Sampling Point: Water Plant Finished Water

PWS ID: Not Supplied

EEA Methods									
Analyte ID #	Analyte	Method	Reg Limit	MRL†	Result	Units	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537	—	90	< 90	ng/L	11/10/14 07:30	11/11/14 04:19	3133280
375-85-9	Perfluoroheptanoic acid (PFHpA)	537	—	10	10	ng/L	11/10/14 07:30	11/11/14 04:19	3133280
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537	—	30	< 30	ng/L	11/10/14 07:30	11/11/14 04:19	3133280
375-95-1	Perfluorononanoic acid (PFNA)	537	—	20	< 20	ng/L	11/10/14 07:30	11/11/14 04:19	3133280
1763-23-1	Perfluorooctane sulfonate (PFOS)	537	—	40	< 40	ng/L	11/10/14 07:30	11/11/14 04:19	3133280
335-67-1	Perfluorooctanoic acid (PFOA)	537	—	20	440	ng/L	11/10/14 07:30	11/11/14 14:06	3133280

Sampling Point: Well #7 Raw Water

PWS ID: Not Supplied

EEA Methods									
Analyte ID #	Analyte	Method	Reg Limit	MRL†	Result	Units	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537	—	90	< 90	ng/L	11/10/14 07:30	11/11/14 04:50	3133281
375-85-9	Perfluoroheptanoic acid (PFHpA)	537	—	10	10	ng/L	11/10/14 07:30	11/11/14 04:50	3133281
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537	—	30	< 30	ng/L	11/10/14 07:30	11/11/14 04:50	3133281
375-95-1	Perfluorononanoic acid (PFNA)	537	—	20	< 20	ng/L	11/10/14 07:30	11/11/14 04:50	3133281
1763-23-1	Perfluorooctane sulfonate (PFOS)	537	—	40	< 40	ng/L	11/10/14 07:30	11/11/14 04:50	3133281
335-67-1	Perfluorooctanoic acid (PFOA)	537	—	20	450	ng/L	11/10/14 07:30	11/11/14 14:37	3133281

Sampling Point: Well #3 Raw Water

PWS ID: Not Supplied

EEA Methods									
Analyte ID #	Analyte	Method	Reg Limit	MRL†	Result	Units	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537	—	90	< 90	ng/L	11/10/14 07:30	11/11/14 05:20	3133282
375-85-9	Perfluoroheptanoic acid (PFHpA)	537	—	10	< 10	ng/L	11/10/14 07:30	11/11/14 05:20	3133282
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537	—	30	< 30	ng/L	11/10/14 07:30	11/11/14 05:20	3133282
375-95-1	Perfluorononanoic acid (PFNA)	537	—	20	< 20	ng/L	11/10/14 07:30	11/11/14 05:20	3133282
1763-23-1	Perfluorooctane sulfonate (PFOS)	537	—	40	< 40	ng/L	11/10/14 07:30	11/11/14 05:20	3133282
335-67-1	Perfluorooctanoic acid (PFOA)	537	—	20	170	ng/L	11/10/14 07:30	11/11/14 05:20	3133282

Client Name: Village of Hoosick Falls

Report #: 328480

Sampling Point: Well #6 Raw Water

PWS ID: Not Supplied

EEA Methods

Analyte ID #	Analyte	Method	Reg Limit	MRL†	Result	Units	Preparation Date	Analyzed Date	EEA ID #
375-73-5	Perfluorobutanesulfonic acid (PFBS)	537		90	< 90	ng/L	11/10/14 07:30	11/11/14 05:51	3133283
375-85-9	Perfluoroheptanoic acid (PFHpA)	537		10	< 10	ng/L	11/10/14 07:30	11/11/14 05:51	3133283
355-46-4	Perfluorohexanesulfonic acid (PFHxS)	537		30	< 30	ng/L	11/10/14 07:30	11/11/14 05:51	3133283
375-95-1	Perfluorononanoic acid (PFNA)	537		20	< 20	ng/L	11/10/14 07:30	11/11/14 05:51	3133283
1763-23-1	Perfluorooctane sulfonate (PFOS)	537		40	< 40	ng/L	11/10/14 07:30	11/11/14 05:51	3133283
335-67-1	Perfluorooctanoic acid (PFOA)	537		20	280	ng/L	11/10/14 07:30	11/11/14 05:51	3133283

† EEA has demonstrated it can achieve these report limits in reagent water, but can not document them in all sample matrices.

Reg Limit Type: MCL SMCL AL
Symbol:

Lab Definitions

Continuing Calibration Check Standard (CCC) / Continuing Calibration Verification (CCV) / Initial Calibration Verification Standard (ICV) / Initial Performance Check (IPC) - is a standard containing one or more of the target analytes that is prepared from the same standards used to calibrate the instrument. This standard is used to verify the calibration curve at the beginning of each analytical sequence, and may also be analyzed throughout and at the end of the sequence. The concentration of continuing standards may be varied, when prescribed by the reference method, so that the range of the calibration curve is verified on a regular basis.

Internal Standards (IS) - are pure compounds with properties similar to the analytes of interest, which are added to field samples or extracts, calibration standards, and quality control standards at a known concentration. They are used to measure the relative responses of the analytes of interest and surrogates in the sample, calibration standard or quality control standard.

Laboratory Duplicate (LD) - is a field sample aliquot taken from the same sample container in the laboratory and analyzed separately using identical procedures. Analysis of laboratory duplicates provides a measure of the precision of the laboratory procedures.

Laboratory Fortified Blank (LFB) / Laboratory Control Sample (LCS) - is an aliquot of reagent water to which known concentrations of the analytes of interest are added. The LFB is analyzed exactly the same as the field samples. LFBs are used to determine whether the method is in control.

Laboratory Method Blank (LMB) / Laboratory Reagent Blank (LRB) - is a sample of reagent water included in the sample batch analyzed in the same way as the associated field samples. The LMB is used to determine if method analytes or other background contamination have been introduced during the preparation or analytical procedure. The LMB is analyzed exactly the same as the field samples.

Laboratory Trip Blank (LTB) / Field Reagent Blank (FRB) - is a sample of laboratory reagent water placed in a sample container in the laboratory and treated as a field sample, including storage, preservation, and all analytical procedures. The FRB/LTB container follows the collection bottles to and from the collection site, but the FRB/LTB is not opened at any time during the trip. The FRB/LTB is primarily a travel blank used to verify that the samples were not contaminated during shipment.

Matrix Spike Duplicate Sample (MSD) / Laboratory Fortified Sample Matrix Duplicate (LFSMD) - is a sample aliquot taken from the same field sample source as the Matrix Spike Sample to which known quantities of the analytes of interest are added in the laboratory. The MSD is analyzed exactly the same as the field samples. Analysis of the MSD provides a measure of the precision of the laboratory procedures in a specific matrix.

Matrix Spike Sample (MS) / Laboratory Fortified Sample Matrix (LFSM) - is a sample aliquot taken from field sample source to which known quantities of the analytes of interest are added in the laboratory. The MS is analyzed exactly the same as the field samples. The purpose is to demonstrate recovery of the analytes from a sample matrix to determine if the specific matrix contributes bias to the analytical results.

Quality Control Standard (QCS) / Second Source Calibration Verification (SSCV) - is a solution containing known concentrations of the analytes of interest prepared from a source different from the source of the calibration standards. The solution is obtained from a second manufacturer or lot if the lot can be demonstrated by the manufacturer as prepared independently from other lots. The QCS sample is analyzed using the same procedures as field samples. The QCS is used as a check on the calibration standards used in the method on a routine basis.

Reporting Limit Check (RLC) / Initial Calibration Check Standard (ICCS) - is a procedural standard that is analyzed each day to evaluate instrument performance at or below the minimum reporting limit (MRL).

Surrogate Standard (SS) / Surrogate Analyte (SUR) - is a pure compound with properties similar to the analytes of interest, which is highly unlikely to be found in any field sample, that is added to the field samples, calibration standards, blanks and quality control standards before sample preparation. The SS is used to evaluate the efficiency of the sample preparation process.